

PRO POWER SERIES



*Picture shown may not represent exact model. Consult factory.

PPS4042LG 4GPM@4200PSI



PEP1313G8 PUMP



PP420 Engine

Standard Accessories

- ◆ Gun/wand assembly
 - ◆ 25' hose w/ couplers
 - ◆ Chemical injector
 - ◆ 3 color-coded QC spray nozzles
 - ◆ 1 color-coded QC chemical nozzle
- NOTE:** 2700-3300 PSI models include 22mm twist coupler socket hose ends; 4200 PSI models include 22mm twist socket x 3/8" QC plug hose ends.

Available Options

- ◆ Skid Mount – precede model with S/, Example: S/PPS4042LAI.
- ◆ 50' Hose Upgrade – add -50 suffix to model, Example: PPS2533HAI-50

Standard Features

- ◆ Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- ◆ Lifetime frame warranty
- ◆ 50 mesh inlet filter
- ◆ Adjustable pressure unloader
- ◆ Low oil shutdown Kohler, LCT & GX models only
- ◆ Pneumatic tires
- ◆ Dual padded shock absorbing feet
- ◆ 3/4" cold-rolled steel axle
- ◆ Kohler SH, Honda GC Series consumer grade & GX Series commercial grade engines are 50 state approved
- ◆ LCT Maxx Series commercial grade 49 state approved engines – **Not available in CA.**
- ◆ Thermo-sensor (prevents overheating in bypass mode)
- ◆ All models meet or exceed PWMA standards of +/- 10%.

Pressure-Pro®