HOT SHOT SERIES



4230VB-20G3

4GPM@2000PSI

230V/3PH/12A **5.0HP**



Standard Accessories

- Gun/ wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Adjustable high pressure chemical metering system
- ◆ 4 color-coded QC spray nozzles

Available Options

- ATK010 Inline Adjustable Thermostat
- ♦ BRK100 Brake Kit
- HRK415 Hose Reel Kit, 150' x 3/8" max.
 w/ no add'l hose
- AR and CAT pumps available consult factory



EM3613T Motor

Standard Features

- Rugged powder coated steel roll cage frame
 w/ lifting hook & 13" flat free tires & threaded
 axles
- ◆ 4-wheel dimensions "39" L x 31" W x 49" H
- Super efficient schedule 80 coil w/ one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- ♦ 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade motors
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Low speed pump w/ thermo-sensor (prevents over heating in bypass mode)
- ♦ 12′ power cord (no GFCI or Plug)